

4.5 Synthesis

Synthesis is simply design. Design is the creative process that we use to develop solutions to requirements, thereby employing systems engineering (SE) to satisfy operational needs. In the Synthesis process, we first conceive and then later refine specific designs to satisfy operational needs.

Synthesis defines design solutions and identifies systems that satisfy the requirements baseline. Synthesis translates requirements, as set in context by the Functional Architecture, into the design architecture, consisting of the Physical Architecture with its associated technical requirements. The resulting architecture provides an arrangement of system elements by designing their composition and interfaces, both internal and external. Additionally, the design architecture incorporates environmental, technical, and other constraints.

Synthesis is seldom, if ever, a one-step process, but rather accomplished many times over the life of a project in response to many factors, such as newly evolving technology, test data from the present or previous designs, changes in requirements from the user, changes in the price or availability of components, feedback from the field once a system is deployed, and so on. As with all SE functions, different objectives and activities exist within different phases of the acquisition process.

4.5.1 Introduction

The Synthesis process is only a portion of the overall SE discipline, with other processes occurring before, during, and after. Synthesis also leverages efforts conducted under various Specialty Engineering (Section 4.8) disciplines through concurrent engineering. Accordingly, Synthesis requires a number of inputs into the process to achieve the anticipated results, or outputs, of the process. See Figure 4.5-1.

Synthesis is conducted to translate the requirements (based on the Functional Architecture) into a Physical Architecture by defining the system elements. These elements are then refined and integrated into the system's physical configuration, which satisfies the functional and performance requirements. This process relies heavily on prior establishment of clearly defined, documented, and validated requirements.

When entering the Synthesis process, do not assume that the entire requirements set associated with the functional area under consideration is achievable within the cost and schedule constraints. However, do assume that all requirements associated with the functional area under consideration have been validated in accordance with Validation and Verification (Section 4.12). The engineers involved in Synthesis are challenged to find the best possible solution that optimizes achievement of the requirements baseline for the functional area under consideration. This requires close and continual coordination with Requirements Management (Section 4.3) and Functional Analysis (Section 4.4).

Success of the Synthesis or design process relies on a structured and disciplined approach to achieving the desired outcomes. Synthesis outputs naturally emerge from taking the appropriate steps during the conduct of design. Conducted properly, Synthesis may define the build-to characteristics of the system or system elements. The Configuration Items are established and defined during Synthesis. At each level of the resulting design architecture, the requirements and interfaces shall be verified. The Synthesis process shall not only identify

technically feasible and programmatically achievable design alternatives, but these alternatives shall be well analyzed, documented, and finally placed under disciplined management.




Figure 4.5-1: The Synthesis Process; Inputs, Tasks, and Outputs

4.5.2 Process Inputs

The Synthesis process starts at the conclusion of a number of preceding key SE steps, as illustrated in Figure 4.5-2. These SE processes result in a number of outputs that serve as necessary inputs to Synthesis.

Like Synthesis, the processes preceding it are not necessarily one-step processes. Each may undergo a number of iterations through the given process before the output is ready for the next process to begin. Additionally, the Requirements Management (Section 4.3) and Functional Analysis (Section 4.4) processes are tightly coupled, and a few iterations through these processes occur before readiness to proceed into Synthesis.

Once Synthesis begins, it works as an iterative process, at times initiating iteration back through Requirements Management, and known as the requirements verification loop. Synthesis might also at times initiate iteration back through Functional Analysis, known as the design loop. During these iterative loops through preceding processes, the requirements baseline and/or Functional Architecture are constrained and refined to optimize the potential for viable design alternatives. This ensures that the Functional Architecture and requirements at lower levels of the Physical Architecture reflect the envisioned design.




Figure 4.5-2: Requirements and Architecture Definition

4.5.2.1 Initial Inputs

The inputs resulting from the previously conducted SE processes are known as the initial inputs, as they serve to initiate Synthesis. They shall be available before system design begins.

4.5.2.1.1 Functional Architecture

During Functional Analysis (Section 4.4), the high-level functions are decomposed to lower-level functional groups or areas that can be satisfied by system design alternatives. The Functional Architecture shall describe the functional arrangements and sequencing of subfunctions resulting from decomposition. The Functional Architecture does not consider design solutions, but only tasks that the solution(s) shall perform. Synthesis, by contrast, considers the grouped and decomposed functions, or functional areas, in light of technically feasible and achievable solutions.

Functional Analysis provides the design group the appropriate area of the Functional Architecture at which to begin the design process. This Functional Architecture is translated into an established requirements set that documents the problem or set of problems to be solved by Synthesis. The problem for the design group is to identify and define a system or systems that adhere to the prescribed Functional Architecture while meeting stakeholder requirements.

4.5.2.1.2 Requirements Baseline

The user needs and system functions are translated into a set of clearly defined, prioritized, measurable, and validated requirements (Section 4.3) for which the design group shall provide a

94 solution or solution set. The established requirements baseline dictates the tasks that the
95 system(s) under design shall perform through functional requirements. The baseline also
96 dictates how well the system(s) shall perform its tasks through documented performance
97 requirements. And finally, the requirements baseline ensures system compliance, function, and
98 performance through measurable verification requirements on the Requirements Verification
99 Compliance Document (RVCD).

100
101 Not only is information needed regarding what the system shall perform, how well it is to be
102 performed, and how performance is to be measured, but the baseline also establishes the
103 system's limitations. The requirements baseline contains the constraint requirements levied on
104 potential solutions. Design constraints further limit the ability of the system under design from
105 reaching its desired level of achievement. System design usually faces limitations. Therefore,
106 design constraints shall be identified, documented, and managed so that they do not manage
107 design by default. The constraints determine the output of the system under design, whether or
108 not they are acknowledged.

109
110 During the Synthesis process, the limitations of engineering shall themselves be considered.
111 Often, solutions are limited by "the laws of physics" or state of the art. The design group
112 undertaking the Synthesis process needs to clearly understand technical as well as
113 programmatic limitations in order to trade risk, schedule, and financial constraints in overcoming
114 challenges to satisfying the requirements baseline.

115 **4.5.2.1.3 Legacy System Definitions**

116 In the FAA, it is rare when a solution is introduced into a pristine environment (i.e., an
117 environment in which a system is not already satisfying user needs.) It is also rare that
118 established needs do not evolve and change as the operational environment also evolves and
119 changes. Consequently, it is important to understand the existing legacy system that currently
120 seeks to satisfy documented needs.

121
122 Understanding shall include knowledge of the legacy system functions, performance, and its
123 shortfalls. Only then can the design solution provide an alternative that improves existing
124 capabilities, adds new functionality, and complies with evolving user needs. All documentation
125 regarding system functional, performance, and constraint requirements is therefore a necessary
126 input into the Synthesis process.

127
128 The design constraints imposed by the need to operate with existing interfacing systems shall
129 also be understood. Interface Control Documents provide the information needed to ensure
130 integration into the existing environment.

131
132 Finally, the new system shall eventually operate in the existing support environment.
133 Documentation regarding legacy system maintenance and support is needed to ensure that the
134 system is designed in a manner that enables it to continue to perform the needed user tasks at
135 the needed level of performance once introduced into the support system.

136 **4.5.2.1.4 Integrated Program Plan**

137 The Integrated Program Plan (IPP), an output of the Integrated Technical Plan (Section 4.2)
138 group, is the document within the Acquisition Management System that provides the plans for
139 the detailed actions and activities necessary to execute the program within the cost, schedule,
140 and performance baselines. The IPP encompasses all elements of program implementation.
141 This may include the acquisition of systems and equipment, construction or modification of

facilities and the physical infrastructure, functional integration of planned capabilities within the existing infrastructure, and procurement of services.

To perform Synthesis, one shall also know the schedule or budget constraints, provided as clearly documented input. If the program phase is such that an IPP exists, it is to provide this needed information. If such a plan does not exist, the design team has to determine the cost and schedule constraints through interface with program management and other stakeholders.

4.5.2.1.5 Operational Services and Environment Description (OSED)

The OSED provides operational, safety, performance, and interoperability requirements. (See Functional Analysis (Section 4.4).) This document provides needed information for the Synthesis process. The OSED identifies the desired air traffic services and or capabilities and their operational environments, including documented operational functions, performance expectations, and selected technologies. It defines the customer needs so that more appropriate alternative selections are feasible during Synthesis.

4.5.2.1.6 Preliminary Work Breakdown Structure (WBS)

A preliminary WBS is provided and initially guides Synthesis efforts. (See Integrated Technical Planning (Section 4.2).) It is then refined under Synthesis by incorporating the characteristics necessary to support the functional and selected Physical Architecture(s) of potential design alternatives. The WBS defines categories of work, work packages, and, ultimately, through Synthesis the identification of associated physical elements. The WBS is invaluable from the planning and management perspective as it establishes a top-down framework for allocating and computing costs. The WBS assists in tracking the status of engineering efforts, resource allocations, cost estimates, expenditures, and cost and technical performance.

During Synthesis, the WBS shall be scrupulously maintained and finalized to show in a hierarchical manner all work elements needed to complete a given program or project. As solution Physical Architectures are defined, the physical elements are introduced into the WBS.

4.5.2.2 Other Inputs

Beyond the inputs available from SE processes occurring prior to Synthesis, there are inputs to be gathered during Synthesis from sources both internal and external to the SE process.

4.5.2.2.1 Market Research

Market research is conducted during Synthesis to gather data necessary to conduct the process and for various reasons. During various stages of the Acquisition Management System (AMS) cycle, the role of market research in the Synthesis process varies.

The first time through the Synthesis loop, when an initial requirements database has been established (initial Requirements Document) and provided as input to the Synthesis process, market research helps to determine the available technologies or various systems that can meet all or part of the requirements baseline.

If multiple viable alternatives do not exist, the baseline and Functional Architecture are to be modified for optimization of alternative solutions. This optimization may occur numerous times as needed. During the final Synthesis iteration, the requirements baseline is finalized (final Requirements Document) and market research is conducted in concert with the design team to identify vendors who meet all requirements of the finalized baseline.

One final and important consideration for market research is to determine the market base for proposed design alternatives. A smaller potential market base for a system and/or its components inevitably translates to an increase in cost risk and a greater potential for the market not to continue to produce the needed items for the needed timeframes as the demand for the supply diminishes. Market research is therefore valuable in determining not only what is available in the market place, but also in determining the extent of its availability and the likelihood of it continuing to be available for the required project/program lifecycle for which Synthesis is to provide a solution.

4.5.2.2.2 Risk Mitigation Plans

Risk Mitigation Plans, although invaluable, may or may not be available for a given iteration through the Synthesis loop. The initial time through the Synthesis loop, finalized requirements baseline and Functional Architecture, are not available. Therefore, the risks associated with potential design alternatives are undefined, and concerns and issues associated with those risks are not yet forwarded to risk management by the Synthesis team.

Subsequent iterations through the Synthesis loops will have incorporated those initial concerns and issues; however, and a risk mitigation plan will have been developed under risk management (in concert with the Synthesis process).

4.5.2.2.3 Trade Study Reports

Trade Study reports are invaluable, whether available to the Synthesis process from previous related efforts or whether solicited through the course of the process. The Trade Study report provides documented answers to many issues and concerns for the Synthesis process, such as feasibility of design alternative, state of technology to support the alternative, and so on.

Existing Trade Study reports may identify related technologies that Synthesis may consider for incorporation into design alternatives. These existing reports provide valuable insight into what is feasible given the current state of the art.

When the Trade Study is conducted in concert with Synthesis, it is geared toward exploring and determining feasibility, associated risks, maturity of design, conformance to the requirements baseline and Functional Architecture, and adherence to the various constraints to the program/project. This input is solicited in the sense that the Synthesis process works in concert with the trade study process to determine objectives and needed outcomes for the Trade Study report. (See Trade Studies (Section 4.6).)

4.5.2.3 Summary of Needed Input for Synthesis

The availability of data depends on the status of the Synthesis process. If it is the first-time entry into Synthesis, or the first Synthesis loop, not all data becomes available. However, as the Synthesis process continues, more data becomes available from other SE disciplines. Table 4.5-1 summarizes the data that is required for the Synthesis process and its availability.

Table 4.5-1: Needed Synthesis Data

Input	Delivering Process	SEM Reference	Availability
Requirements Baseline	Requirements Management	Section 4.3	1st and subsequent loops
Functional Architecture	Functional Analysis	Section 4.4	1st and subsequent loops
Legacy System Specifications	External to SE	N/A	1st and subsequent loops
Legacy Interface Requirements	Interface Management	Section 4.7	1st and subsequent loops
Draft IPP	Integrated Technical Planning	Section 4.2	1st Synthesis loop
Operational Services and Environment Description	Functional Analysis	Section 4.4	1st and subsequent loops
Preliminary WBS	Integrated Technical Planning	Section 4.2	1st Synthesis loop
Market Research	External to SE	N/A	May not be available 1st loop through Synthesis
Trade Study Report	Trade Studies	Section 4.6	May not be available 1st loop through Synthesis
Risk Mitigation Plans	Risk Management	Section 4.8	May not be available 1st loop through Synthesis

4.5.3 Process Steps

The activities of Synthesis involve selecting a preferred solution or arrangement from a set of alternatives and understanding associated cost, schedule, performance, and risk implications. Synthesis entails undertaking a number of necessary and distinct steps geared toward achieving measurable goals and objectives while striving to manage or overcome constraints. Alternative candidate designs are first conceptualized; candidate alternative solutions are then defined and refined in order to meet the established requirements baseline.

Engineering analysis is used, as necessary, to evaluate alternatives. Evaluation identifies, assesses, and quantifies risks and selects proper risk-mitigation approaches. The risk management plan, if available, is utilized to refine the various design alternatives and achieve a balance between risk and technical progress. Too much risk within a given alternative could result in an unachievable design at the end. Assuming too little risk within a given alternative could also result in a solution that cannot be reached within the schedule constraints established for the project. These two extremes are balanced against the requirements baseline and established Functional Architecture through the guidance provided in the Risk Mitigation Plan(s). (See Integrated Technical Planning (Section 4.2).)

The analysis of alternative solutions also results in an understanding of cost, schedule, and performance impacts. As subsystem requirements are defined, the identification of the needs, requirements, and constraints for lifecycle processes is completed. The specific tasks that define Synthesis are identified in Figure 4.5-3.




Figure 4.5-3: The Synthesis Process Activities

Synthesis demands creativity in order to achieve success. The ability to discover new solutions, to look at the requirements from new perspectives, and to formulate new concepts from two or more previously held ideas challenges the design group during this process. In order for the

design group to succeed, each individual member of the team shall exercise awareness and sensitivity to problems associated with each proposed approach. They shall exercise flexibility, originality, self-discipline, and persistence while maintaining adaptability, nonconformity, tolerance for ambiguity, self-confidence, and a healthy skepticism.

In addition to exercising necessary individual characteristics, the team shall also be aware of necessary group characteristics and dynamics essential for the successful development of achievable yet satisfactory design alternatives.

A group of “like-thinkers” typically arrives at a mutually agreeable solution, or solution set, in less time and with less discourse than a diverse group with differing perspectives and priorities. The solution reached in this relatively pain-free manner may not have always considered and analyzed every facet of the approach and all problems associated with it. As a result, the solution may not in the end satisfy all the requirements and design constraints levied on the Synthesis process. The devil’s advocate plays an important role in the group and is as equally important to achievement of the group’s goals, as is the consummate politician.

Once a diverse and well-balanced group is formed, the group can begin to develop design alternatives and a set of prioritized objectives through a variety of methods. The group can use such methods as brainstorming, brainwriting, and dynamic confrontation (see text box at right). Whatever method or combination of methods is selected for this creative development of alternatives, care is to be exerted to ensure that no one individual is allowed to dominate the group and, therefore, its outcomes. Likewise, care shall also be exerted to ensure that every member of the group is given ample opportunity to contribute to the group’s efforts.

Brainstorming

This technique involves both idea generation and idea reduction. First idea generation occurs by simply identifying as many solution ideas as possible. Later in idea reduction those potential solutions are ranked into groups, with a specific group encompassing those potential solutions considered most useful to the group.

This technique is frequently considered a powerful one as it often results in the most creative and effective solutions. These solutions may arise from a combination of seemingly unrelated ideas, generated early in the process. Brainstorming encourages creative and original thinking.

Brainwriting

This technique builds on the concept of brainstorming, as it is the same technique but simply replaced verbal communication with writing. Utilizing this technique, team members write down a number of relevant ideas on a sheet of paper (usually limited to three ideas). The paper is then passed to another team member who then develops those ideas. New ideas and elements are added to the original concept(s) and the augmented pages are then passed onto another team member.

This process continues until each team member receives back the sheet of paper containing the original concepts they created. At this point the beginning phase is complete and a group leader collects all idea/solution sheets.

The next phase is then commenced with all the sheets being handed out to the entire group. The group then works to revise the ideas developed in the prior phase.

This technique alleviates one of the problems associated with brainstorming in that dominant members may not easily steer the efforts of the entire group.

Dynamic confrontation

This technique is an adversarial group process. The main idea in this technique is for team members to criticize every idea. A presentation is first made and then every element and assumption of that idea is intensely challenged. This technique tests out every idea thoroughly and forces all members to thoroughly think through and develop their ideas.

4.5.3.1 Requirements Review and Objectives Definition—Step 1

After ensuring that all needed available Synthesis data is together (see Table 4.5-1), Synthesis begins with a review of the requirements baseline and the Functional Architecture in order to understand what is to be performed and at what level of performance to meet stakeholder

needs. Requirements Management does not dictate *how* the stakeholder needs are to be met. The design Synthesis process determines how to achieve stakeholder needs.

Establishing objectives assists in optimizing adherence to the requirements set within the technological and programmatic limits imposed on the design process. Objectives shall be linked to stakeholder needs and system requirements. Objectives take into consideration operational criteria, mission success, technical performance, cost, schedule, quality, risk, failure rate, maintainability, and supportability. Through definition and prioritization of all design solution objectives, the optimal solution is achieved that best satisfies the requirements set under consideration.

Often, devices perform their functions at varying performance levels in differing environments. For instance, the system delay for a computer system gathering surveillance data from various sources and formulating a graphical representation of all existing air vehicles in a given space and presenting it to the controller on a display is vastly different at various locations and at various times during the day. Stakeholders would only state minimum NAS requirements for presentation of data to them from the source. The engineers involved in Synthesis shall decide how they are to meet those stated requirements in the various environments. A tailored system for each location might be provided, thus lowering the overall cost of upfront procurement, as computer systems with less processing power may be utilized in small airport areas. However, the training and support regarding multiple systems shall also be addressed in terms of added cost for multiple versions of the system. In this example, the Synthesis engineers shall evaluate the operating environment of the solution to determine what the objectives are for performance, upfront procurement cost, and the lifecycle costs of supporting the resulting system. These items represent three distinct objectives to be satisfied in selecting a design that fulfills the stakeholder needs.

Another facet to consider is that a single system design may not necessarily satisfy all of the requirements associated with the functional area under consideration. Multiple systems may be required to satisfy the entire requirements set.

Ideally, it is recommended that alternative solutions satisfy all requirements, but it is useful to include solutions that challenge the requirements and lead to a better system concept. Various options are to be considered eventually in light of the objectives for the resulting system(s). Such alternatives include relaxing requirements of marginal utility that are costly to implement or extending requirements when added capability can be purchased cheaply while resulting in operational benefits.

4.5.3.1.1 Performance Objectives

The performance objectives, although highly dependent on potential system solutions, shall be clear, as they serve to define the main purpose of the system. The engineering team shall not only define all terms that measure how the system performs, but the actual desired performance levels shall also be stated. The accuracy, capacity, response time, throughput, and other similar requirements are reviewed and analyzed against feasible design possibilities. The threshold performance levels are clearly documented for the design under consideration. Most, if not all, of the performance requirements are contained in the requirements baseline provided under Requirements Management. However, the stated performance objectives that are to be achieved by any potential system or systems are clearly documented at the outset of Synthesis so that the tradeoff between these and other objectives may follow.

4.5.3.1.2 Reliability Objectives

The reliability objectives shall be defined in terms of the likelihood, or probability, that the resulting system will operate at its objective performance level for a defined period of time under normal operating conditions. To clearly define the reliability objectives, engineers shall translate the environmental and operational data as contained in the OSED. Allocation of the RMA requirements in the requirements baseline is conducted in concert with the requirements process and Specialty Engineering in order to allocate the various reliability maintainability objectives to the various design alternative functional areas.

4.5.3.1.3 Compatibility Objectives

The engineering team shall define the objectives for the system to work, or interface, with both existing systems and those under agency development. Interface objectives are stated in terms of not only the data and physical interface, but also in terms of the working environment imposed by the existing systems or system elements with which the potential design alternative shall interact. The objectives shall address both backward compatibility with legacy systems and forward compatibility with known evolving technologies, protocols, and standards.

4.5.3.1.4 Extensibility Objectives

The engineering team shall define the objectives to allow for alternative design approaches to be able to adjust to a changing environment. For example, the ability to process more flight data to adapt to a growth in air traffic shall be clearly defined and documented. This is particularly important when it is known that the existing environment is to evolve. As the environment evolves, so shall any design alternative evolve to adapt to the new environment. Projections for changes are documented along with the stated objectives for extensibility of the design alternative.

4.5.3.1.5 Flexibility Objectives

Flexibility differs from extensibility, which means the ability to adapt to and accommodate growth needs. Flexibility is the ability of the design alternative to serve new or multiple uses. An example of flexibility is a multipurpose display that provides graphical display of flight plan data, surveillance data, or both simultaneously without need for modification.

4.5.3.1.6 Cost Objectives

A limited budget is a never-ending facet of the Synthesis process. Thus, it is essential to define clearly at the outset the cost objectives for any potential design alternative. Try not to overemphasize cost of the item over all other objectives. The old adage, "You get what you pay for," is all too often true. Consequently, cost objectives are best stated as a range within which the design alternatives shall reside. Cost objectives shall include all facets of the potential design alternatives' lifecycle. Restricting objectives merely to the initial cost of a design solution may not fairly consider other design alternatives that have higher initial cost, but whose overall lifecycle costs are lower due to quality, reliability, and supportability characteristics. Therefore, the cost objectives shall be defined for all stages of the intended lifecycle.

4.5.3.1.7 Schedule Objectives

What a design alternative does, how well it performs the function(s), and where it performs become irrelevant if the design alternative is not delivered to the user when needed. A design alternative delivered before its time is as potentially damaging to the effort as one delivered too late. Therefore, the schedule objectives for all facets of the design alternatives' lifecycle shall be defined clearly and comprehensively. The schedule objectives for test, operational introduction, full operational capability, service life, and so on are all documented.

4.5.3.1.8 Objectives Tradeoffs and Hierarchy Definition

Rarely, if ever, are projects faced with unlimited time and financial resources. Tradeoffs and compromises are common during Synthesis in order to achieve the design objectives with an acceptable level of requirements compliance. It is essential to define the design objectives and rank their relative importance.




Figure 4.5-4: Example Three-Level Objectives Hierarchy

The prioritized set of objectives, defined during the brainstorming, brainwriting, and dynamic confrontation meetings, is to be well established and documented before design solutions are considered.

Objectives in both the above categories and additional categories to be

considered under the program/project are first documented as a list. The list is expanded to include more categories as determined necessary in concert with program management, Specialty Engineering, and stakeholders. The importance of each objective relative to the others is then determined for all objectives. Once all the relative priorities are established, priority levels are defined based on the findings. This task, although not simple, is necessary, as the results are invaluable later when design alternative tradeoff analysis is performed.

Assume that each of the categories in Section 4.5.3.2 has one objective; there are then a total of seven resulting objectives. For this example, examine a project that eliminates a reliability deficiency in an existing fielded system. In this particular example, RMA is therefore considered of higher importance than all other alternatives. Also, as the product introduced is only an interim solution to fulfill a shortfall, system flexibility is considered less important than all other factors. If all remaining objectives are considered to be of equal importance, there are three priority levels (Figure 4.5-4)




Figure 4.5-5: Example Four-Level Hierarchy

Establishing the objectives hierarchy is seldom this simple. The items in level two of the figure are rarely seen as equal in importance. This level may be further broken down into groups, with

each group containing objectives of equal importance and with one group being considered to be more important than the other. This leaves four levels of priorities instead of three, and the hierarchy is established, complete with relative objective priorities, and priority-level definition (Figure 4.5-5).

4.5.3.2 Define Design Solution Set—Step 2

During this Synthesis step, grouping of needed functions into common functional areas is complete and the Functional Architecture is established. The design team shall now begin partitioning desired functional requirements into design elements. During review of various designs in terms of whether or not they will perform the desired functions, each function in the Functional Architecture is mapped to a component of the system under review. Some components may perform only one function; others may perform more functions (Figure 4.5-6).




Figure 4.5-6: Functional Partitioning to System Components

This Synthesis process step boils down to generating alternative design solutions for the functional elements identified during Functional Analysis (Section 4.4) that perform the needed functions and adhere to the requirements for that functional area. It is recommended that the alternative solutions be composed of one or a combination of more than one of the following: hardware, software, material, data, facility, people, and techniques.

There are a variety of tasks conducted to identify various design alternatives. Various subteams may perform the tasks sequentially or concurrently. If the Synthesis group is small, the preferred choice is for all members to look at identifying alternatives sequentially. If the group is large enough and good communications exist among all members, the option to concurrently identify solutions by the various means described below is worth exploring. Both approaches require that the entire group conduct prior planning. Concurrent exploration of alternatives requires close coordination throughout identification of alternatives until all possibilities are identified; whereupon, the subteams may once again combine to complete this Synthesis step. Figure 4.5-3 illustrates the tasks feeding the Synthesis step that identifies the various design alternatives.

4.5.3.2.1 Technology Assessment

This assessment addresses not only potential incorporation of existing technology into design solutions, but also looks at the risks and limits imposed by and on that technology. Each alternative under consideration is analyzed against the changing technologies available in the marketplace. Available technologies are studied for use in the design under consideration, potential improvements to design performance, improvement to maintainability of the resulting system, cost-effectiveness, and maturity.

The need for a new technology that makes possible a performance or functional improvement not previously possible shall be carefully weighed against the risk imposed by that technology. The potential benefits of inserting the technology shall outweigh the potential risks to cost, schedule, and performance.

To continue consideration of the potential technology insertion, the impacts to the end user shall be considered through human factors analysis. The tasks, roles, and jobs assigned to humans are analyzed and assessed to discover whether the end users of the resulting system have the required knowledge, skills, and abilities. If the needed knowledge, skills, and abilities do not exist, then the cost and schedule risks of achieving them with the new technology are weighed against the benefits derived from the technology. Training and personnel pipelines are fully evaluated to ensure that they meet requirements.

4.5.3.2.2 Identify Specialty Engineering Attributes

The design team shall work in concert with specialty engineers to identify the characteristics of each potential alternative necessary to fulfill interdisciplinary needs.

The design team works in concert with safety engineers to analyze each alternative, and to identify potential hazards to the hardware/software components of the system, the humans involved in the system as users and support personnel, or the environment. The analysis shall demonstrate that the design under consideration results in safe system operations. All aspects of the design, development, manufacture, test, operation and support of the potential design are included in the analysis.

The design team works in concert with human engineering to analyze each alternative for human factors suitability. Each alternative is analyzed with respect to the human user system interface. (See Specialty Engineering (Section 4.8).)

4.5.3.2.2.1 System Safety Engineering

System hazards are identified and assessed for the design alternative. The hardware, software, operational, and ambient environments, and procedures and human elements of the design alternative are analyzed, and historical or test data is applied to estimate the risk (severity and likelihood) of each identified hazard. Controls are then designed in accordance with the safety order of precedence described in Specialty Engineering Section 4.8.1. All hazards and their associated controls are prioritized according to their risk criticality rating. The analysis results are used to direct further design efforts to characterize the system's controls, safety features, redundancy, and degradation elements.

4.5.3.2.3 Off-the-Shelf Opportunities

Each design alternative is analyzed to determine if an off-the-shelf item exists that fulfills the allocated requirements. Off-the-shelf solutions may include non-developmental hardware or software.

Once off-the-shelf solutions are identified, each shall undergo assessment to ensure that a variety of factors are considered in determining suitability. The number of systems available off the shelf shall be gauged against the number users need. The quantity needed shall encompass not only those needed initially by the user community, but also those needed to serve as replacements over the anticipated service life of the system.

Another facet of the suitability assessment process is consideration of the environment in which the prospective off-the-shelf item shall eventually operate. The ability of the proposed item to adapt to the existing support structure is a necessary component in determining its suitability. If the item requires new equipment and/or training for support during its lifecycle, the benefits of the item shall outweigh its cost and schedule impacts.

Finally, the manufacturer(s) of the off-the-shelf item shall undergo assessment. Attributes such as product maturity, upward/downward compatibility, manufacturer track record, financial stability, and quality practices shall be factored into the commercial product selection process. If the products or manufacturers fall short in any of the reviewed categories, they shall be considered a risk. Refer to Appendix F of the FAA COTS Risk Mitigation Guide for a more detailed listing of COTS nontechnical selection factors.

4.5.3.2.4 Make-or-Buy Alternatives

A cost analysis is performed for the design alternative(s) and used to support a make-or-buy decision. This analysis needs to address whether it is more cost-effective to produce the design element versus using an established supplier.

When cost, schedule, and risk are considered, it is most beneficial to design and develop (a “make” decision) a peculiar system that satisfies all requirements of the functional area. The team may proceed with this approach as a viable design alternative.

4.5.3.3 Identify Alternatives for Design Solution—Step 3

Input from preceding processes and previous Synthesis steps identify not only potential alternatives, but also design constraints for potential solutions. This input helps determine if existing or newly developed items can accomplish the functional element under consideration.

Synthesis strives to identify viable design alternatives, refine those alternatives to fulfill the requirements baseline, and finally select the most balanced and beneficial design to introduce into the field. To accomplish this goal, all possible alternatives are first identified. These are reduced to reflect only those alternatives considered viable or worth pursuing.

4.5.3.3.1 Populate the Solution Set

The design team identifies all possible design solutions that may serve to satisfy all or part of the requirements baseline. At first, it is merely an exercise in exploring all possibilities. Once the team has exhausted all possibilities, the design solution set is evaluated both as a group and individually. If only one possible design alternative has been identified, then the job is not complete. No matter how large or difficult the requirements baseline and the functional area with which it is associated, there always exists at least one possible design alternative: *do nothing*. The default is to continue the status quo and not present new and/or innovative design solutions. Given the fact that a great effort went into previous SE processes (such as Requirements Management (Section 4.3) and Functional Analysis (Section 4.4)), it is unlikely that entrance into Synthesis would have occurred if all requirements in the functional area, with its associated requirements baseline, were satisfactorily met. Clearly, it is possible to identify an insufficient number of alternatives. The task is to develop additional alternatives that present better options.

The following methods can be used to develop new alternatives.

- **Change the characteristics of existing alternatives.** First, list all existing alternatives. For each alternative in the list, itemize its main characteristics. Generate a table with the rows representing the list of alternatives and the columns representing the main characteristics of all alternatives. In all likelihood, each of the potential alternatives possesses characteristics that are both similar and distinct from those of the other alternatives. The positive characteristics are identified. Missing characteristics needed by a design alternative and not represented by any potential solution are then listed. Finally, more alternatives are then added to the list, as the characteristics within the previously listed alternatives are varied, enhancing the new alternatives with needed positive characteristics and eliminating as many negative characteristics as possible.
- **Go back to the objectives.** Focus on the most important objectives one at a time. List alternatives that meet each of those top-level objectives. Then, work down the objectives hierarchy, developing more alternatives or refining existing alternatives that satisfy those additional objectives.
- **Finally, look at all the objectives and requirements set.** List alternatives that maximize the number of objectives and requirements that are able meet with the alternative.

If there still seems to be lack of viable alternatives, step through the various methods, introducing more creativity and ingenuity each time through. Eventually, a solution set reaches a stable point, and identification of design alternatives is complete.

Now that a significant number of design alternatives are identified, all alternatives are evaluated. First, determine that a number of sound viable design alternatives exist that can satisfy all or most of the baselined requirements. It is possible to continue the Synthesis process with too many design alternatives, as the remaining steps detail and document each alternative to a great degree. Therefore, proceeding with too many alternatives can waste valuable time and resources. One can argue that proceeding with one alternative is not sufficient. Likewise, one might also argue that proceeding with 10 alternatives that shall be thoroughly defined and documented is an unnecessary excess; so reduction of the alternatives set to a manageable size or number (based on the scope of the stakeholder need) of alternatives shall occur.

4.5.3.3.2 Reduce Solution Set to Manageable Number of Alternatives

When viable design solutions are identified, compromise of requirements considered absolutely necessary to satisfy the operational needs shall not occur. Those requirements considered so important to satisfying the user needs that a system not meeting them is deemed unnecessary or unacceptable are to be considered “*threshold requirements*.” A potential design solution shall satisfy threshold requirements for further consideration as a design alternative. Threshold requirement compromise or tradeoff is not an option for consideration. A design alternative not meeting a threshold requirement that cannot be modified easily to meet the requirement(s) is eliminated and not considered further.

The objectives hierarchy is used next. If the remaining alternatives set contains potential solutions that do not meet the top-level objectives, and they cannot be easily or affordably modified to do so, then those alternatives are eliminated from the set of potential alternatives. As with requirements, some objectives are not subject to compromise, and it is recommended

that alternatives not meeting the high-priority objectives, as defined earlier, no longer be considered.

If potential solutions are only able to satisfy a portion of the functional area requirements or objectives, consider various options to develop a set of viable design solutions. One or more of the solutions that nearly satisfy the objectives and/or requirements could be modified to achieve satisfactory results. The following options may be used to modify either the problem (functional area under consideration with its associated requirements) or the alternative design solutions:

- **Trade Study Request.** To determine if one or more of the options can be modified to fulfill the desired requirements and/or objectives, a detailed analysis, such as that conducted under Trade Studies (Section 4.6) is requested. Under the Trade Studies process, incorporation of new technologies and a variety of other means are investigated. If the results of the study render viable design alternatives, then Synthesis proceeds into the next step, requirements allocation. However, if it turns out that no alternative can meet all of the requirements in the functional area under consideration, the requirements and/or the functional areas are analyzed.
- **Initiate Requirements Feedback.** When the requirements baseline for the functional area under consideration cannot be satisfied through viable design alternatives, feedback to Requirements Management (Section 4.3) is initiated. If requirements are only partially met by all potential designs, the ability to meet the requirements set is analyzed concurrently by Synthesis and Requirements Management. Consideration is given to modifying requirements to lower and achievable levels. Full compliance is deferred until technological or other advances allow for full compliance with the original requirements. Requirements that cannot achieve even partial compliance in the various designs are addressed through the design loop.
- **Initiate Design Feedback.** Due to discovery of design issues, the Functional Analysis (Section 4.4) is reexamined, and the initial decomposition or performance allocations are reassessed. Design issues include identifying a promising physical solution or open-system opportunities that have different functional characteristics than those foreseen by the initial Functional Architecture requirements. Issues also include the inability of all design alternatives to fulfill the same functional area requirements, which may be addressed by repartitioning of the functional area. The functional area is subdivided so that allocation of those requirements to be satisfied by the alternative designs are made down to perspective system elements. The remaining functional areas whose associated requirements are not to be satisfied remain with the Functional Analysis (Section 4.3) process. The associated requirements are documented as unsatisfied in the Requirements Management (Section 4.3) process. The functional area(s) with the associated unsatisfied requirements are partitioned out of Synthesis, back to Functional Analysis for future Synthesis loop identification of potential solution(s).

Review and analysis of all remaining alternative solutions are conducted in concert with Specialty Engineering, risk management, lifecycle engineering, and integrated program planning in order to determine adequacy and suitability of each remaining alternative. The alternatives are pared down to preferred design solutions.

4.5.3.4 Allocation to System Elements—Step 4

The previous Synthesis steps have resulted in a promising set of conceptual designs for systems satisfying the requirements baseline for the functional area under consideration. Each design concept shall now be developed in more detail so that requirements and design constraints are assigned to the top-level elements of that system design.

4.5.3.4.1 Allocation of Requirements to System Elements

In prior steps, the functional area and associated requirements were adjusted in concert with Functional Analysis and Requirements Management, respectively. As this Synthesis step is entered, the requirements to be satisfied by the design solution(s) are established, and this step furthers the design process by allocating the requirements to system elements.

These elements are the highest-level distinct elements of the system in the areas of hardware, software, and humans in the system. Each system element shall perform at least one function within the functional area to be considered separately and distinctly in the traceability of requirements.

The design engineers proceed in allocating requirements to the selected system elements. All requirements that the system shall satisfy are documented, and formal tracking of those requirements through the various design and acquisition phases of the system begins. Documentation includes information regarding the hardware, software or other components of the system to which each requirement is allocated.

4.5.3.4.2 Allocation of Design Constraints to System Elements

Design constraints that apply directly to system elements are identified. These constraints do not apply to the functions performed, but rather the elements: hardware, software, or people. Design constraints differ from constraint requirements in that they recognize existing limitations to design of a system, its interfacing systems, and its operational and physical environment. Such design constraints include power, weight, data throughput rates, memory, and other resources. These constraints represent the inability to achieve a capability or level of performance due to such issues as technology, and available facility space for the system.

Design constraints are especially important in analyzing the design of potential replacements for existing systems. This is of particular interest to design engineers when major elements of the original system may be retained. The design constraints once allocated clearly defines which system elements remain, are added, or modified.

Those technology constraints identified during the prior technology assessment are to be allocated to the system elements. Those constraints identified during review of Specialty Engineering attributes are allocated to ensure that inappropriate design characteristics are not introduced into the selected system. Finally, environmental constraints are allocated down to the system element level. Environmental constraints may be introduced by climatic conditions in which the total system is to operate, by the facilities in which the system is to be housed, or more globally by environmental hazards and constraints (such as Environmental Protection Agency regulations) imposed in the region(s) where the systems is to be used.

4.5.3.5 Define Design and Performance Characteristics—Step 5

With the system concepts now defined, identify the design and performance characteristics of each alternative. Once defined, the design and desired performance characteristics are

documented. The system(s) characterization is all-inclusive and addresses all facets of the system under design, including the associated human-engineering elements and lifecycle considerations or needs.

During this phase, there is strong benefit to practice concurrent engineering. The entire functionality of the system(s) under design is considered. When the design and performance characteristics are defined, the entire lifecycle of the potential system shall be considered, from inception to disposal, in an integrated process. This requires involvement of all Specialty Engineering disciplines (Section 4.8) in the Synthesis process. Thus, sound engineering decisions are made based on strong consideration of all phases and aspects of the system under design consideration.

4.5.3.5.1 Assess failure modes, effects, and criticality

Failure modes, the effects, and the criticality of failure are assessed for the design alternative. The hardware, software, and human elements of the design alternative are analyzed and historical or test data is applied to estimate the probability of successful performance of each alternative. Use a failure modes and effects analysis to identify the strengths and weaknesses of the design solution (See Reliability, Maintainability, and Availability Engineering (Section 4.8.2).) For critical failures, a criticality analysis is conducted to prioritize each alternative by its criticality rating. The analysis results are used to direct further design efforts to characterize redundancy and graceful system degradation elements of the system.

4.5.3.5.2 Assess testability needs

The testability of the design is analyzed in relation to the operational or maintenance needs. The team determines the need for a built-in test, Remote Maintenance Monitoring, and/or a fault-isolation test for each potential design alternative. For elements that are normally maintained by the users or field support engineers, test mechanisms are considered in the design and incorporated as necessary. Diagnostic operations to support lower-level maintenance actions are likewise incorporated into the design solution.

4.5.3.5.3 Standardization Opportunities

The alternative is assessed for possible use of standardized end items that are technologically and economically feasible. Use of design elements that implement commercial and international standards is strongly considered.

4.5.3.5.4 Lifecycle Factors Assessment

The design of each alternative is assessed to determine the degree to which quality factors (producibility, ease of distribution, usability, supportability, trainability, and disposability) have been included in the solution. Additionally, associated lifecycle process needs, requirements, and constraints are identified and defined for each design under consideration. (See Lifecycle Engineering (Section 4.13).)

4.5.3.6 Physical Architecture Definition—Step 6

A Physical Architecture defines and describes the way in which the various Functional Architecture elements can be brought together to form physical entities. The physical entities shall represent a viable design alternative and shall provide one or more services that address user needs as translated by the requirements baseline. The Physical Architecture may involve such physical entities as runways and various forms of equipment; such nonphysical entities as software; or a combination of the two.

The Physical Architecture identifies the physical subsystems, and architecture flows between subsystems that implement the functions and provide the needed services/capabilities. The Physical Architecture further identifies the system inputs and outputs.

In constructing a Physical Architecture, the following definitions are used:

- **Physical Entities.** The classes of physical entities used are:
 - Subsystems. Subsystems are the primary structural components of the Physical Architecture. They perform functions that “belong” together and whose interfaces require interoperability and compatibility.
 - Users. These are people who interact with the architecture implementation. They could either be those who use the system (such as the flying public or pilots in the NAS) or operators who use features of the system (such as air traffic controllers in the NAS). Each interface to a user involves human interaction with the system.
 - External Systems. These are organizations and agencies and/or their systems that may likely interact/interface with the system under design (such as DoD or National Weather Service to the NAS).
 - Environment. This is the physical world, such as pavement, air, obstacles, and so on.
- **Physical Interfaces.** These are mechanical, electrical, data, and other interfaces between system elements or subsystems. Physical interfaces also include all interfaces between the system and its outside world.

4.5.3.6.1 Decomposition into Physical Entities

The architecture can be viewed at several levels of detail. The architecture defines collections of subsystems while defining their interfaces. Consideration is given to a variety of engineering and programmatic disciplines along with stakeholder contributions, and all are incorporated into the Physical Architecture.

4.5.3.6.2 Physical Interfaces Definition

Identify and define the physical interfaces among products, subsystems, humans, lifecycle processes, and external interfaces to higher-level systems or interacting systems. Physical interfaces that impact design include communication, data, support, test, control, display, connectivity, or resource replenishment characteristics of the interaction among subsystems, the products, humans, or other interfacing systems or a higher-level system (See Interface Management (Section 4.7).)

4.5.3.7 Design Alternative Analysis and Refinement—Step 7

As a particular design alternative is refined, it is analyzed to determine how it satisfies the allocated functional and performance requirements, interface requirements, and design constraints and how it adds to the overall effectiveness of the system or a higher-level system. During analysis, specialty engineers work with design engineers to ensure that requirements such as reliability, availability, maintainability, supportability, safety, human factors, security, electromagnetic compatibility, and spectrum management are incorporated into the design.

Additionally, lifecycle process requirements are identified and defined for each alternative system product solution and aggregate of solutions.

4.5.3.7.1 Assess design capacity to evolve

The design alternative is analyzed with respect to its capacity to evolve or be reengineered, accommodate new technologies, enhance performance, increase functionality, or incorporate other cost-effective or competitive improvements once the system is in production or in the field. It is recommended that limitations that may preclude the ability of a system to evolve be identified and the approach analyzed and refined to resolve any limitations. The supportability of an evolving system may require the support process to evolve along with the product. This consideration may significantly affect support funding and training requirements.

4.5.3.7.2 Develop models and prototypes

Models and/or prototypes are developed to assist in:

- Identifying and reducing risks associated with integrating available and emerging technologies
- Verifying that the design solution (made up of hardware, software, material, humans, facilities, techniques, data, and/or service) meets allocated functional and performance requirements, interface requirements, workload limitations, and constraints
- Verifying that the design solution satisfies Functional Architecture and baseline requirements

The models, data files, and supporting documentation are maintained, and each version of a model or data file that impacts requirements, designs, or decisions saved in the integrated database. Models may be digital, partial, or complete and may be hardware, software, or a combination of both, or may include human models or human-in-the-loop simulations or mockups for usability testing and workload measurement. (See Trade Studies (Section 4.6).)

4.5.3.8 Check Requirements Compliance—Step 8

Compliance with the requirements baseline for the functional area is reviewed and analyzed. For each alternative, the solution level of compliance to all requirements is documented. If full compliance is not reached by any of the alternatives, and they all fail to meet the same requirements, the design loop is initiated. If some, but not all, of the alternatives fail to fully meet all of the requirements, and compliance varies among approaches, the requirements feedback loop is initiated for each design. This is not to be confused with Verification (Section 4.12).

4.5.3.8.1 Design Loop

The design loop involves revisiting the Functional Architecture to verify that the Physical Architecture developed is consistent with the functional and performance requirements. It is a mapping between the functional and Physical Architectures. During design Synthesis, reevaluation of the Functional Analysis may be caused by discovery of design issues that require reexamination of the initial decomposition, performance allocation, or even the higher-level requirements. These issues might include identification of a promising physical solution or open-system opportunities that have different functional characteristics than those foreseen by the initial Functional Architecture requirements.

4.5.3.8.2 Requirements Feedback Loop

The system design is audited to determine compliance with the requirements set. Audits are performed at various levels, from the top-level Physical Architecture down through each hierarchy level to the lowest-level system element or configuration item. Compliance with the requirements is assessed through both informal and formal reviews. The audit results are then fed back to earlier Synthesis steps as needed, resulting in another Synthesis loop. The audit results may call for requirements changes at varying levels, or they may lead to design changes to ensure compliance.

4.5.3.9 Select Preferred Design Solution—Step 9

The best alternative solution is selected using all prior analysis conducted in Synthesis or in conjunction with Requirements Management (Section 4.3), Functional Analysis (Section 4.4), Trade Studies (Section 4.6), Specialty Engineering (Section 4.8), and Risk Management (Section 4.10). The selected solution shall be the one that offers the most balanced design. Upon being selected, the design is detailed and finalized. The designation and description of interfaces (internal and external) among design elements are finalized. The design is baselined and placed under formal configuration management processes.

4.5.4 Process Outputs

It bears repeating that Synthesis is an iterative process, concurrent with Functional Analysis (Section 4.4) and Requirements Management (Section 4.3). The engineering team shall use good judgment in aligning the degree of detail of the Synthesis outputs with the position of the project in the AMS cycle.

Prior to the selection of the preferred design solution, Synthesis outputs are completed concisely and at a very high level for *all* possible solutions. As the functional analysis and baseline requirements become more specific, there are fewer and fewer alternative solutions that answer the need. As the process narrows to the “best” solution, the top choices have detailed, documented outputs from the Synthesis team. Once the Joint Resources Council chooses the preferred solution, the Synthesis team completes the definition of the design process to the finest detail.

Therefore, the following Synthesis outputs occur throughout the iterative process, but vary in scope and level of detail based on the project’s position within the AMS cycle.

4.5.4.1 Physical Architecture

For all the alternative solutions, the system elements are identified along with their arrangement and the interactions between them. A description of the salient features of the overall solution is developed as well as descriptions for the system elements and their relationships establishing a potential System Architecture baseline. The descriptions are diagrams, schematics, concept drawings, tabular data, and narrative reports.

The design architecture is established at a level appropriate to document the design solution and interfaces. It includes the requirements traceability and allocation matrices, which capture the allocation of functional and performance requirements among the system elements. It is recommended that design architecture definitions be stored in the integrated database along with tradeoff analysis results, design rationale, and key decisions to provide traceability of requirements up and down the architecture. It is recommended that verification of the design architecture be accomplished to demonstrate that the architecture satisfies both the validated

requirements baseline and the verified Functional Architecture. This information is further compiled into a Requirements Compliance Matrix.

4.5.4.2 Description of Alternatives

4.5.4.2.1 Concept Description Sheets

A separate description for each of the alternatives developed and refined during Synthesis is documented. For the selected or preferred design, more detail is provided, such that other SE processes can best utilize the information. A complete description of the system, the system operational use, and characteristics is documented in the description sheets.

4.5.4.2.2 Architecture Block Diagrams

The hierarchical relationship of all system elements is to be documented in an Architecture Block Diagram (ABD). The ABD includes hardware and software elements and their hierarchy, documentation and data, facilities, test equipment, and support.

An external ABD is also to be developed to depict the external elements that affect the selected system. It is recommended that the external ABD, like the system ABD, include all hardware, software, facilities, personnel, data, and services having a significant effect on the selected system.

4.5.4.2.3 Schematic Block Diagrams

Schematic Block Diagrams (SBD) illustrate the physical partitioning and interfaces for each candidate hardware and software design solution determined to be viable. It is recommended that SBDs not be developed for every conceivable design, but only for those that are worthy of detailed evaluation (based on position within AMS cycle).

4.5.4.2.4 Interface Drawings

Drawings are developed for all system physical element interactions. Additionally, all interactions to external physical elements are also documented in drawings. The drawings provide the visualization of interfaces and are the basis by which interface specifications and control documents are developed later under Interface Management (Section 4.7).

4.5.4.3 Integrated data package

The drawings, schematics, software documentation, manual procedures, and so on are developed as necessary to document the selected design elements in an integrated data package.

4.5.4.3.1 Configuration Item Descriptions

Each of the system elements are identified during the Synthesis process. This includes all hardware configuration items (HWCI) and computer software configuration items (CSCI). Documentation and description of each HWCI and CSCI occurs at identification of the item in summary or preliminary fashion. Once a final design alternative is selected, detailed documentation for each HWCI and CSCI of the selected system is developed, thus establishing a configuration baseline for the system (See Configuration Management (Section 4.11)).

4.5.4.3.2 Specification Inputs

During Synthesis, compliance with the requirements baseline (RVCD) was assessed. This analysis sometimes results in recommendations for requirements modification or elimination. Any proposed modifications or deletions are documented and forwarded to Requirements Management (Section 4.3).

4.5.4.3.3 Requirements Compliance Matrix

All requirements have been mapped to the system elements. As the mapping occurred during Synthesis, a matrix was developed containing all requirements, the subsystem or element to which they were assigned, and the level of adherence to the requirements achieved by the component. The matrix is designed for each level of the Physical Architecture, and all performance, functional, and constraint requirements are listed in the matrix to reflect each level of the architecture. Compliance levels are determined using system/cost-effectiveness analysis, simulations, demonstrations, inspection, and or testing.

4.5.4.3.4 Refined Work Breakdown Structure

The selected design's Physical Architecture is used to refine the Work Breakdown Structure (WBS) by translating the decomposition into a WBS format. The refined WBS provides enhanced work planning, cost/schedule tracking, and control by extending the existing WBS to account for the system elements identified during Synthesis.

4.5.4.4 Constraints

Constraints are formed before entering the Synthesis process, and yet more may be identified during the process. Synthesis looks at many different aspects of the system design, including cost, scheduling, feasibility, requirements, function and others. As various solutions to the MNS are considered and refined, constraints become apparent.

Constraints are clearly seen when performing step 4 of the Synthesis process, Allocation of Requirements to System elements (Paragraph 4.5.3.5.1). The constraints identified may cause iteration through the design feedback loop or the Requirements feedback loop. An evolutionary development is initiated, if necessary, for any design element for which a lesser technology solution was selected over a higher-risk technology, and for which the capacity to evolve was designed into the element and interfacing elements. (See Trade Studies (Section 4.6).)

4.5.4.4.1 Design Constraints

Constraints specific to the Synthesis process, design constraints, are identified and documented in step 5 (see Paragraph 4.5.3.5.2). These constraints do not apply to the functionality of the system, rather they are in the area of hardware, software, or people. Because these design constraints are so important in analyzing replacement of existing systems, they are documented and sent on for further study in the Lifecycle Engineering process (Section 4.13), aiding in identifying the timing of future replacement schedules. Additionally, these design constraints become another output of the Synthesis process, as requests for Trade Study (Section 4.6) evaluation are sent out.

4.5.4.5 Planning Criteria

Planning criteria describing planned activities for the Synthesis process are output to the Integrated Technical Planning process (Section 4.2).

4.5.4.6 Tools/Analysis Requirements

Tools/Analysis Requirements for performing Synthesis throughout the remainder of the program's lifecycle need to be provided to the Integrity of Analysis process (Section 4.9).

4.5.4.7 Concerns/Issues

Appendix D contains guidance on Concerns/Issues as a product of Synthesis and how to best convey that information to the Risk Management team (Section 4.10).

4.5.4.8 Planning Criteria

Planning criteria describing planned activities for the Synthesis process are output to the Integrated Technical Planning process (Section 4.2).

4.5.5 Metrics

Performance of the Synthesis process itself shall be measured on a regular basis and recorded in the metrics library on a monthly basis. The following metrics, at a minimum, may be used to evaluate performance:

1. Trade Study Satisfaction Assessment (see Trade Studies (Section 4.6))
2. For approved engineering problem reports:
 - a. Quantity, by type of problem report
 - b. Cycle-time from disposition to incorporation of change into released engineering documents, by type of report
3. Technical Performance Measurements: objective versus achieved values
4. Number of approved engineering changes: by product, type, and stage
5. Documents/drawings submitted for engineering release:
 - a. Unacceptable submittals
 - b. Total submittals
6. Number of technical action items identified during reviews and audits
7. Design efficiency metrics, such as weight, required power, and envelope dimensions (volume)
8. Cost and schedule variance for the completion of Synthesis steps
9. System requirements not met
10. Number or percent of system requirements verified by system analyses
11. Number of TBDs in system architecture or design
12. Number of interface issues not resolved

13. Percent of identified system elements that have been defined

4.5.6 Tools

4.5.6.1 Schematic Block Diagrams (SBD)

Along with the definition of design alternatives, it is important to establish the relationships between alternatives at each level of design activity. A medium for accomplishing this is by using SBDs.

A simplified SBD shows the components that may comprise an element and the data that may flow between them. An expanded version is usually developed that displays the detailed functions performed within each component and their interrelationships. For complex systems, this may then be developed into a logic diagram for auditing the schematics produced. This audit is a critical SE function. It is recommended that Interface information also be embedded into the SBDs, as appropriate. The interface data forms the basis for the interface specifications to be developed at multiple levels of the system hierarchy. An N² diagram (see Functional Analysis (Section 4.4) for examples) is very useful for developing and auditing interfaces at all levels.

If software is an element of the design, it shall be determined whether a given function is to be accomplished in hardware or software. It is recommended that Computer Software Elements (CSE) be defined during this step of the process and embedded within the SBDs. Experience shows that it is helpful to first define the top-level HWCI and/or CSCI in which a given software function is to reside before defining which candidate CSEs may accomplish the function. Additionally, as part of Section 4.5.3.7 of the Synthesis process (Physical Architecture definition), it is recommended that a given function be tracked to determine whether it has been allocated to a software alternative or a hardware alternative. Determining the appropriate level of the system hierarchy for defining CSEs is largely project dependent.

The products of this step of the SE process are a set of viable system alternatives responsive to the design goals and a series of SBDs depicting how the alternatives interrelate.

4.5.6.2 Computer-Aided Design

Modern computing hardware and software is used to convert the initial idea for a system into a detailed engineering design. The evolution involves creating geometric system models that are later manipulated, analyzed, and refined.

4.5.7 References

1. Defense Systems Management College. "Systems Engineering Fundamentals." Fort Belvoir, VA: Defense Systems Management College Press, 1999
2. EIA Interim Standard, Systems Engineering Capability Model, EIA/IS-731.1, December 1998
3. EIA Standard, Processes for Engineering a System, EIA-632, January 7, 1999
4. Guidelines for Approval of the Provision and Use of Air Traffic Services Supported by Data Communications, RTCA/DO-264, Prepared by SC-189, December 14, 2000
5. Handbook of Systems Engineering and Management, Andrew P. Sage and William B. Rouse, ©1999

- 1099 6. IEEE Standard for Application and Management of the Systems Engineering Process,
1100 IEEE Std-1220-1998
- 1101 7. International Council on Systems Engineering. "Systems Engineering Handbook,"
1102 Version 2.0, 2000
- 1103 8. ITS Physical Architecture Physical Architecture, Lockheed Martin Federal Systems,
1104 Odetics Intelligent Transportation Systems Division, September 1998
- 1105 9. KAREN Physical Architecture Physical Architecture, Version 2, Siemens Traffic Controls
1106 Limited, October 1999
- 1107 10. Systems Engineering Management, Second Edition, Benjamin S. Blanchard, ©1998
- 1108 11. Systems Engineering Guidebook, A Process for Developing Systems and Products,
1109 James N. Martin, ©1997
- 1110